



PLANARGARD® NMB CARTRIDGE FILTERS

Sub 32 nm node CMP slurry filtration with leading edge of "Nanofiber Continuous Melt-blown" technology

Overview

The Planargard® NMB CMP slurry filter is constructed of a new polypropylene membrane technology that produces a continuous-melt-blown (CMB) fiber in-depth media structure. The CMB technology enables yield improvement in both bulk slurry and point-of-use applications at sub 32 nm nodes.

Nanofiber Continuous Melt-blown Technology

Planargard NMB filters contain nanofibers and multi-layer CMB media for an improved flow path with high retention. The large gradients design can increase particle-loading capacity and lower-face-velocity due to increased media porosity, providing a long lasting filter performance without compromising the filter retention performance.

Target Application

- Ceria and colloidal silica bulk slurry filtration
- Sub-fab CDS filtration




Features and Benefits

Features	Benefits
Various retention rating	Applicability to many slurry processes, including pre-filtration and final filtration in slurry manufacturing
Nanofiber CMB technology	Better defect reduction performance at the same rating
Optimized graded depth structure	Lower cost of ownership
High-volume filter manufacturing	Consistent and high quality
	Short lead time to customers


Specifications

Materials:	Membrane	Polypropylene
	Support	Polypropylene
	Cartridge o-ring	EPR, Silicon, 2-222
Product type:	NMB	
Maximum operating conditions:	Maximum temperature	80°C (176°F)
	Maximum forward differential pressure	0.48 MPa (4.8 bar, 70 psi) @ 25°C (77°F)

Dimensions




Size	A	B
10"	240 mm ±2 mm (9.45" ±0.08")	263 mm ±2 mm (10.35" ±0.08")
20"	494 mm ±2 mm (19.45" ±0.08")	517 mm ±2 mm (20.35" ±0.08")
30"	748 mm ±3 mm (29.45" ±0.12")	771 mm ±3 mm (30.35" ±0.12")
40"	1002 mm ±3 mm (39.45" ±0.12")	1024 mm ±3 mm (40.31" ±0.12")




Size	A	B
10"	240 mm ±2 mm (9.45" ±0.08")	251 mm ±2 mm (9.88" ±0.08")
20"	494 mm ±2 mm (19.45" ±0.08")	505 mm ±2 mm (19.88" ±0.08")
30"	748 mm ±3 mm (29.45" ±0.12")	758 mm ±3 mm (29.84" ±0.12")
40"	1002 mm ±3 mm (39.45" ±0.12")	1013 mm ±3 mm (39.88" ±0.12")

Performance Data



Ordering Information

Part Number



For More Information

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit www.entegris.com and select the Customer Service link for the center nearest you.

Terms and Conditions of Sale

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit www.entegris.com and select the Legal Notices link from the footer.

Entegris®, the Entegris Rings Design® and Planargard® are registered trademarks of Entegris, Inc.

ENTEGRIS, INC.

Corporate Headquarters | 129 Concord Road | Billerica, MA 01821 USA
Customer Service Tel. +1 952 556 4181 | Customer Service Fax +1 952 556 8022
In North America 800 394 4083 | www.entegris.com

©2010-2012 Entegris, Inc. All rights reserved Printed in USA 4423-6028ENT-1212

