

# WAFERGARD® GT-PLUS AND GTL IN-LINE GAS FILTERS

Remove particles from inert gases for flow rates up to 80 SLPM

#### Overview

Wafergard® GT-Plus in-line gas filters are designed to remove particles from inert gases for flow rates up to 30 SLPM. Wafergard GTL in-line gas filters are designed for flow rates up to 80 SLPM. Both filters provide efficient, low-cost point-of-use filtration of inert gases.

### **Applications**

- Low air intake filter
- Wafer transport systems
- Clean dry air (CDA)



Wafergard GTL gas filters




Wafergard GT-Plus gas filters

## Specifications

		GT-PLUS	GTL
Membrane:		Hydrophobic Teflon® fluoropolymer PTFE	Hydrophobic Teflon fluoropolymer PTFE
Supports/housings:		PFA	Polysulfone
Recommended flow rate:		30 SLPM	80 SLPM
Connections:		1/8", 1/4" compression seal	Rc¹/4 (PT¹/4 female), ¹/4" NPT female
Dimensions:	Length	1/8" seal: 69 mm (2.7")	101 mm (4.0")
		1/4" seal: 71.5 mm (2.8")	
	Diameter	21.5 mm (0.85")	25 mm (0.98")
Maximum operating pressure:		0.41 MPa (4.1 bar, 56.6 psid) @ 20°C	0.41 MPa (4.1 bar, 56.6 psid) @ 20°C
Maximum forward differential pressure:		0.34 MPa (3.4 bar, 50 psid) @ 20°C	0.41 MPa (4.1 bar, 56.6 psid) @ 20°C
Maximum reverse differential pressure:		0.03 MPa (0.3 bar, 4.35 psid) @ 20°C	0.03 MPa (0.3 bar, 4.35 psid) @ 20°C
Maximum operating temperature:		50°C (122°F)	50°C (122°F)
Membrane area:		12 cm² (1.9")	25 cm² (3.9")
Particle retention:		>99.9999999% removal of all particles greater than 0.003 µm diameter (verified at the most penetrating particle size)	>99.9999999% removal of all particles greater than 0.003 µm diameter (verified at the most penetrating particle size)

#### Performance Data



### **Ordering Information**

Part Number (3/pack)	Part Number (10/pack)	Wafergard GT-Plus
WGFG 01K P3	WGFG 01K P0	1/8" compression seals
WGFG 21K P3	WGFG 21K P0	1/4" compression seals
Part Number (5/pack)	Accessory	
JPMFJK001	6.34 mm (1/4") PFA compression ferrules and nuts	
Part Number (10/pack)	Wafergard GT	
WGFG 01D SH	Rc¹/4 (PT¹/4 female)	
WGFG 01D S0	¹/₄" NPT female	



#### For More Information

Please call your Regional Customer Service Center today to learn what Entegris can do for you. Visit *www.entegris.com* and select the Customer Service link for the center nearest you.

### Terms and Conditions of Sale

All purchases are subject to Entegris' Terms and Conditions of Sale. To view and print this information, visit *www.entegris.com* and select the Legal Notices link from the footer.

Entegris®, the Entegris Rings Design® and Wafergard® are registered trademarks of Entegris, Inc. Teflon® is a registered trademark of E.I. du Pont de Nemours and Company.

#### ENTEGRIS, INC.

Corporate Headquarters | 129 Concord Road | Billerica, MA 01821 USA Customer Service Tel. +1 952 556 4181 | Customer Service Fax +1 952 556 8022 In North America 800 394 4083 | www.entegris.com

